

## Thermo Scientific Cimarec Basic Series

Sleek, rugged, no frills design combined with our renowned quality, performance



- Ideal for economical, general-purpose use
- Sleek, rugged design and construction promotes durability
- New top-plate design reduces chance of breakage
- Spill-away design diverts spills away from internal components
- Solid ceramic top plate cleans easily, resists acids and alkalis
- Integral ring-stand holder accommodates 0.5 in. (1.3cm) diameter support rod

**Includes:** TFE-coated stir bar  
**Warranty<sup>Y</sup>:** Three years  
**Certifications:** cCSAus

### Thermo Scientific Cimarec Basic Hotplates

Cat. No.	Surface Area	Top Plate Material	Temp. Range	Overall L x W x H	Electrical
<b>HP194515</b>	10.8 × 10.8cm (4.25 × 4.25in.)	Ceramic	150° to 538°C (302° to 1000°F)	20 × 14.5 × 12.7cm (7.9 × 5.7 × 5in.)	120V 60Hz, 3.21A, 385w
<b>HP194825</b>	18.4 × 18.4cm (7.25 × 7.25in.)	Ceramic	150° to 538°C (302° to 1000°F)	28.2 × 21.1 × 12.7cm (11.1 × 8.3 × 5in.)	120V 60Hz, 8.96A, 1062w

### Thermo Scientific Cimarec Basic Stirring Hotplates

Cat. No.	Surface Area	Top Plate Material	Stirring Range	Temp. Range	Overall L x W x H	Electrical
<b>SP194715</b>	10.8 × 10.8cm (4.25 × 4.25in.)	Ceramic	100 to 2500rpm	150° to 538°C (302 to 1000°F)	20 × 14.5 × 12.7cm (7.9 × 5.7 × 5in.)	120V 60Hz, 3.45A, 405w
<b>SP195025</b>	18.4 × 18.4cm (7.25 × 7.25in.)	Ceramic	100 to 2500rpm	150° to 538°C (302 to 1000°F)	28.2 × 21.1 × 12.7cm (11.1 × 8.3 × 5in.)	120V 60Hz, 9.18A, 1086w

### Thermo Scientific Cimarec Basic Stirrers

Cat. No.	Surface Area	Top Plate Material	Stirring Range	Overall L x W x H	Electrical
<b>S194615</b>	10.8 × 10.8cm (4.25 × 4.25in.)	Ceramic	100 to 2500rpm	20 × 14.5 × 12.7cm (7.9 × 5.7 × 5in.)	120V 60Hz, 0.45A, 21w
<b>S194925</b>	18.4 × 18.4cm (7.25 × 7.25in.)	Ceramic	100 to 2500rpm	28.2 × 21.1 × 12.7cm (11.1 × 8.3 × 5in.)	120V 60 Hz, 0.48A, 23w